

### DESCRIPTION and USES

A heavy-duty, gloss enamel that features very fast dry and a wide color range. Excellent for use as a multi-purpose, fast-drying finish on machinery, equipment, aisle marking or wherever a durable, fast-drying paint is needed. Although this paint has a very fast air dry, it can be forced dry with heat when used as an OEM finish. This paint is suitable for both interior and exterior applications.

### SURFACE PREPARATION

All surfaces must be dry, free of dirt, grease, rust and loose paint. Rough surfaces should be smoothed with sandpaper. Prime bare surfaces with the recommended primer. When painting over previously painted surfaces, apply a small sample area to test for lifting.

### APPLICATION

Best applied with conventional, HVLP or airless spray. Small areas may be rolled or brushed. Use as supplied for brushing. Do not apply at temperatures above 90°F or below 55°F.

### SAFETY INFORMATION

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

For complete safety information, refer to the SAFETY DATA SHEET for this product.

### COLORS

This product is available in White, Black, Safety Orange, and all RepcoLite *Color Renaissance* colors and a nearly infinite variety of custom colors.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

### TECHNICAL DATA

<b>Finish:</b>	High Gloss
<b>Vehicle Type:</b>	Alkyd Resin
<b>Volume Solids:</b>	49% (varies with color)
<b>Coverage:</b>	300 – 400 SF/Gallon (depending on surface and application technique)
<b>Dry Time:</b>	
<i>Touch:</i>	5 – 10 Minutes
<i>Recoat:</i>	3 – 4 Hours (addition of tinting colors may extend dry time.)
<b>Primer:</b>	
<i>Steel:</i>	44810 Metl-Clad QD Rust Inhibitive Primer
<i>Galvanized:</i>	44810 Metl-Clad QD Rust Inhibitive Primer
<i>Wood:</i>	44010 Pro-Flo Primer-Undercoater
<i>Masonry:</i>	44612 Fill-N-Seal Low Temp Acrylic Block Filler
<b>VOC:</b>	Less than 450 g/l
<b>Clean Up:</b>	Xylene

### PRODUCT CODE INFORMATION

40410	Quick Dry Enamel—White
40402	Quick Dry Enamel—212 Base
40403	Quick Dry Enamel—213 Base
40406	Quick Dry Enamel—216 Base
40470	Quick Dry Enamel—Black
40480	Quick Dry Enamel—Safety Orange

**RepcoLite Paints, Inc.**  
473 W. 17<sup>th</sup> St.  
Holland, MI 49423  
(616) 396-1275  
[www.repcolite.com](http://www.repcolite.com)