

DESCRIPTION and USES

A quick dry coating for use on steel, masonry and wood surfaces in commercial buildings, industrial plants and warehouses. Its finish resists dirt and general soil is easily removed from surfaces coated with this paint. It greatly improves the light reflectance in areas where it is used. Because of its quick dry, overspray will usually drop to the floor as a harmless powder that can be picked up by vacuuming or sweeping. This product has very good chemical, moisture and corrosion resistance making it an ideal coating for where these conditions exist.

SURFACE PREPARATION

This product requires a minimum of surface preparation, however surfaces must be dry and as free of dirt and oily substances as possible. Loose and flaking paint should be removed by air blasting.

APPLICATION

Apply with air or airless spray only. Avoid application to cold surfaces, especially during periods of high humidity. In order to maintain compliance with current VOC regulations, DO NOT THIN.

SAFETY INFORMATION

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. This product is for industrial use only. It is not intended for use around a household dwelling.

For complete safety information, refer to the SAFETY DATA SHEET for this product.

COLORS

This product is available in white and light tone colors.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

TECHNICAL DATA

Finish:	Low Sheen
Vehicle Type:	Epoxy Ester/Alkyd
Volume Solids:	44%
Coverage:	200 – 300 SF/Gallon
Dry Time:	
<i>Touch:</i>	30 Minutes
<i>Recoat:</i>	1 Hour
Primer:	
<i>Masonry:</i>	44610 Sprayable Block Filler
<i>Drywall:</i>	44410 Quick Sealer
<i>Plaster:</i>	44110 Prime-All WB Primer
<i>Steel:</i>	44917 Metl-Clad Metal Primer
<i>Wood:</i>	Self Prime
VOC:	Less than 450 g/l
Clean Up:	VMP Naptha

PRODUCT CODE INFORMATION

41514 Dry Mist Heavy Duty Epoxy Ester—White

RepcoLite Paints, Inc.
473 W. 17th St.
Holland, MI 49423
(616) 396-1275
www.repcolite.com