

DESCRIPTION and USES

This flat finish oil-based paint is ideal for use on exterior wood. It is an ideal choice when painting old weathered wood. This paint features easy application and excellent durability, and requires minimal surface preparation. It's low luster finish helps to hid surface defects often found on older buildings.

SURFACE PREPARATION

All surfaces must be dry and free of dirt and dust. Old loose paint must be removed by scraping. Was all protected areas, such as under eaves, with detergent and water, rinsing well and allowing to dry before painting.

APPLICATION

Apply with a paint brush, pad applicator or roller. Spray application may be used where applicable. Do not apply at temperatures under 40°F. On warm, windy days, work in the shade, doing small sections to avoid laps and painting into partially dry areas. Apply as supplied. Thinning this product will bring it out of compliance with current VOC regulations. DO NOT THIN.

SAFETY INFORMATION

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

For complete safety information, refer to the SAFETY DATA SHEET for this product.

COLORS

Barn Red

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

TECHNICAL DATA

Finish:	Flat
Vehicle Type:	Soya Alkyd Resins and Linseed Oil
Volume Solids:	72%
Coverage:	250 – 400 SF/Gallon (depending on surface porosity).
Dry Time:	
<i>Touch:</i>	6 – 8 Hours
<i>Recoat:</i>	24 Hours
Primer:	
<i>Wood:</i>	Self Prime
<i>Metal:</i>	44917 Metl-Clad Primer
VOC:	Less than 350 g/l
Clean Up:	Paint Thinner (Mineral Spirits)

PRODUCT CODE INFORMATION

45920 Red Oil-Based Barn Paint

Repcolite Paints, Inc.

473 W. 17th St.

Holland, MI 49423

(616) 396-1275

www.repcolite.com